


# SPECIFICATIONS



**Model Number:** GL48B7  
**Part Number:** 19031377A

**Version:** 01  
**Mar 25, 2022**

## Mechanical Drawing:



### Motor:

Nominal Voltage = 48 vdc  
 Operating Voltage Range = 36 - 60 vdc  
 Nominal Running Current = 0.31 amps  
 Locked Rotor Current = 0.93 amps  
 Running Power = 14.9 watts  
 Average Speed = 3300 rpm  
 Bearings = Ball  
 Air Flow = 150 CFM  
 Acoustic = 53.6 dBA

### Construction:

Venturi: Die Cast Aluminum, Black  
 Propeller: Plastic, Black, UL 94V-0

### Agency Certifications:

UL, CUL, CE

### Life Expectancy:

This fan is designed for continuous duty life of 60,000 hours at 70°C.

### Additional Features:

Brushless DC Motor  
 Locked Rotor Protection  
 Reverse Polarity Protected  
 Operating Temperature: -10°C to 70°C  
 Storage Temperature: -40°C to 85°C

### Tachometer Output:

Output: 5 volt TTL  
 I<sub>c</sub>: 5 mA Typical  
 Pulses Per Revolution: 2  
 Isolated: No

### Termination:

12" Lead wires, 22 AWG, UL 1061  
 Red = Power (+)  
 Black = Ground (-)  
 Blue/White = Tachometer (Output)

**PQ Curve:**

